

ACCESSORIES



Aluminium Profile
Order Code: AC028-AP
Dimension: 1000x8.9x13.2mm/
39.37"x0.35"x0.52"(LxWxH)
Material: aluminium
Color: silver



Mounting Clips
Order Code: AC020-SET
Dimension: 15x6.8x12.8mm/
0.59"x0.27"x0.50"(LxWxH)
Material: stainless steel
Color: silver
Each meter led strips needs
4 clips + 4 screws



Curved Profile
Order Code: AC019-CR
Dimension: 500x7x12mm/
19.68"x0.28"x0.473"(LxWxH)
Color: silver



Aluminium Profile
Order Code: AC028-SET
Dimension: 25x8.9x13.2mm/
0.98"x0.35"x0.52"(LxWxH)
Material: aluminium
Color: silver



End Cap 2PIN
Order Code: AD016-2-F
Dimension: 8x14mm/
0.31"x0.55"(WxH)
Color: transparent
Cable Entry: front



End Cap 2PIN
Order Code: AD016-2-S
Dimension: 8x14mm/
0.31"x0.55"(WxH)
Color: transparent
Cable Entry: side



End Cap 2PIN
Order Code: AD016-2-B
Dimension: 8x14mm/
0.31"x0.55"(WxH)
Color: transparent
Cable Entry: bottom



Closed End Cap
Order Code: AD017
Dimension: 8x14mm/
0.31"x0.55"(WxH)
Material: silicone
Color: transparent



LEDLINE Scissor
Order Code: AF001-1



Order code: XLG-150-24-A
AC100-305V DC24V 150W
IP67, Global certification.
Non Dimmable.



Order code: ELG-150-24B
AC100-305V DC24V 150W
IP67, Global certification
3in1 dimming function: 0-10Vdc,
10V PWM signal and resistance.



Order code: ELG-150-24DA
AC100-305V DC24V 150W
IP67, Global certification
Dali control technology.

LEDLINE ACE 0612 WHT

APPLICATION

- Facade lighting, contour lighting and landscape lighting.
- Solutions for retail shop.
- Signage and illuminated advertising.
- Ideal for architectural lighting, coves, object integration.

